



Specialised Engineering.
Special Advice.

Certificate of Conformity Watertightness

QA Document Number: ED0046 REV 0

Manufacturer's Address: Gatic
Poulton Close,
Dover,
Kent.
CT17 0UF
Telephone: +44 (0) 1304 203545
Fax: +44 (0) 1304 215001
Web: www.gatic.com

Product Description: Gatic Slotdrain - For the catchment and drainage of surface water in areas for pedestrian and/or vehicular traffic

Product Ranges: CastSlot, CastSlot Treadsafe, UltraSlot, UltraSlot Treadsafe, PaveSlot, FacadeSlot

Load Bearing Capacity: Up to F900*

* When installed in accordance with Gatic's installation details

Material: 1.5/2.5/3mm Thick mild steel sheet grade 'DX51D' (Pre-Galvanised) Continuously hot dipped galvanised 'Z275' minimised spangled, passivated to 'BS EN 10346 : 2009' [DX51D+Z275-M-A-C] (Fe P02 G Z275 MA C).

Applied Standard: EN 1433:2002 + A1 2005

This certificate herewith confirms that the described manufactured items comply with the sections 7.5.1 and 9.3.6 of BS EN 1433:2002 + A1 2005 for linear drainage channels in areas for pedestrian and/or vehicular traffic for the catchment and drainage of surface water, when installed in compliance with the manufacturers installation instructions.

Simon Bradbeer (RD&I Director)

Date: 15/06/2016



FM593418



EMS593419