

GATIC

Declaration of Performance Gatic FacadeSlot



QA Document Number: ED0014 REV. 1

Manufacturer's Address: Gatic
Poulton Close, Dover, Kent, CT17 0UF
Telephone: +44 (0) 1304 203545
Fax: +44 (0) 1304 215001
Web: www.gatic.com

Intended Use: Gatic FacadeSlot - For the catchment and drainage of surface water in areas for pedestrian and/or vehicular traffic.

Product Range: FA00025, FA00026, FA00027
FA00033, FA00034, FA00035
FA00041, FA00042, FA00043

System of Attestation of performance: System 3

Notified Body: NB 0086 - BSI Product Services

Type Test Report No.: 285/4618749

1. Water Tightness - Jointing of Drainage Channels: No Leakage

2. Load Bearing Capacity - Deflection Under Load:

Maximum Load A15*

Permanent Set NPD

3. Durability: NPD

Material: 1.5/2.5/3mm Thick mild steel sheet grade 'DX51D' (Pre-Galvanised) Continuously hot dipped galvanised 'Z275' minimised spangled, passivated to 'BS EN 10346 : 2009' [DX51D+Z275-M-A-C] (Fe P02 G Z275 MA C).

Applied Standard: EN 1433:2002 + A1 2005

This declaration herewith confirms that the described manufactured items comply with the relevant parts of BS EN 1433:2002 + A1 2005 for linear drainage channels in areas for pedestrian and/or vehicular traffic for the catchment and drainage of surface water, *when installed in compliance with the manufacturers installation instructions.

Simon Bradbeer - RD&I Director - Gatic - Poulton Close - Dover - Kent - CT17 0UF

Date: 24/10/2016



FM593418



EMS593419