

# GATIC

## Declaration of Performance Gatic ProSlot



QA Document Number: ED0036 REV. 3

Manufacturer's Address: Gatic  
Poulton Close, Dover, Kent, CT17 0UF  
Telephone: +44 (0) 1304 203545  
Fax: +44 (0) 1304 215001  
Web: www.gatic.com

Intended Use: Gatic ProSlot - For the catchment and drainage of surface water in areas for pedestrian and/or vehicular traffic.

Product Range: A111005, A111010, A111015, A112005, A112010, A121015, A211005, A211010  
A211015, A212005, A212010, A212015, A311005, A312005, A411005, A411010

System of Attestation of Performance: System 3

Notified Body: NB 0086 - BSI Product Services

Type Test Report No.: 2381/7805779

1. Water Tightness - Jointing of Drainage Channels: No leakage

2. Load Bearing Capacity - Deflection Under Load:  
Maximum Load D400  
Permanant Set <1mm  
3. Durability NPD

Material: 1.5mm Thick mild steel sheet grade 'DX51D' (Pre-Galvanised) Continuously hot dipped galvanised 'Z275' minimised spangled, passivated to 'BS EN 10346 : 2009' [DX51D+Z275-M-A-C] (Fe P02 G Z275 MA C).

Applied Standard: EN 1433:2002 + A1 2005

This certificate herewith confirms that the described manufactured items comply with the relevant parts of BS EN 1433:2002 + A1 2005 for linear drainage channels in areas for pedestrian and/or vehicular traffic for the catchment and drainage of surface water, when installed in compliance with the manufacturers installation instructions.

Simon Bradbeer - RD&I Director - Gatic - Poulton Close - Dover - Kent - CT17 0UF

Date: 31/10/2016



FM593418



EMS593419