



Declaration of Performance  
Gatic UltraSlot Treadsafe



QA Document Number: ED0018 REV. 1

Manufacturer's Address: Gatic  
Poulton Close, Dover, Kent, CT17 0UF  
Telephone: +44 (0) 1304 203545  
Fax: +44 (0) 1304 215001  
Web: www.gatic.com

Intended Use: Gatic UltraSlot Treadsafe - For the catchment and drainage of surface water in areas for pedestrian and/or vehicular traffic.

Product Range: UAT00025, UAT00026, UAT00027, UAT00028, UAT00029, UAT00030, UAT00031, UAT00032, UAT00033, UAT00034, UAT00035, UAT00036, UAT00037, UAT00038, UAT00039, UAT00040, UAT00041, UAT00042, UAT00043, UAT00044, UAT00045, UAT00046, UAT00047, UAT00048

System of Attestation of performance: System 3

Notified Body: NB 0086 - BSI product Services

Type Test Report No.: 285/4618749

1. Water Tightness - Jointing of Drainage Channels: No Leakage

2. Load Bearing Capacity - Deflection Under Load:  
Maximum Load F900\*  
Permanent Set NPD

3. Durability: NPD

Material: 1.5/2.5/3mm Thick mild steel sheet grade 'DX51D' (Pre-Galvanised) Continuously hot dipped galvanised 'Z275' minimised spangled, passivated to 'BS EN 10346 : 2009' [DX51D+Z275-M-A-C] (Fe P02 G Z275 MA C).

Applied Standard: EN 1433:2002 + A1 2005

This declaration herewith confirms that the described manufactured items comply with the relevant parts of BS EN 1433:2002 + A1 2005 for linear drainage channels in areas for pedestrian and/or vehicular traffic for the catchment and drainage of surface water, \*when installed in compliance with the manufacturers installation instructions.

Simon Bradbeer - RD&I Director - Gatic - Poulton Close - Dover - Kent - CT17 0UF

Date: 24/10/2016



FM593418



EMS593419